Door Bolts

Sockets, Straps & Strike Plates

A selection of accessories for use with Surface and Flush fitted Door Bolts.



▲ **0600 Dust Excluding Socket** for mastic fixing into wooden floors or cementing into stone floors



0620 Dust Excluding Socket with removable plunger for cleaning & maintenance

	D	d	M (depth	to suit
	(diameter)	(diameter)	of mortice)	shoot size
0600/A	Ø 27	Ø 19	45	Ø 11 max
0600/B	Ø 32	Ø 22	45	Ø 13 max
0620	Ø 45	Ø 22	48	Ø 11 max
0603	-	-	20	Ø 13 max
0604	-	-	20	Ø 13 max



0603 Easy Clean Socket no fixings supplied



0604 Easy Clean Socket supplied with finish matched screws & rawl plugs







For strengthening the fixing of door face fitted Flush Bolts to help prevent doors splitting when inadvertently closed with the Bolt Shoot still thrown.

∧ 5642 Cross Strap for flush bolts (mill finish stainless steel only)





5640ASP Angle Strike Plate designed for use with Ø 11mm flush bolt shoots





Fixings

0603 - no fixings supplied. 0604 & 0620 - supplied with finish matched no.6 x 38mm wood screws & rawl plugs. 5640ASP - supplied with finish matched no.6 x 19mm wood screws. 5642 - supplied with no.6 x 19mm stainless steel wood screws.

How to Order

sclect PRODUCT (c.g. **0620**)
add FINISH (c.g. 0620**PC**)
0600 only - add SIZE (c.g. 0600PB**/A**).

.....

Finishes - See our price list or website for finish availability.

5642 supplied mill finish stainless steel only.

.....

Strike Plates



Fixings

Supplied with finish matched no.6 x 19mm wood screws.

How to Order

select PLATE (c.g. FSP2)
add FINISH (e.g. FSP2/PC)

Finishes - See our price list or website for finish availability.

Staples & Guides



Fixings

Supplied with finish matched wood screws: 04458T, 04548T & type 2 - no.8 x 25mm; type 3 - no.6 x 25mm; type 4 - no.6 x 32mm.

How to Order

l) select ROD GUIDE/STAPLE (e.g. **RG3**)

2) add FINISH (e.g. RG3/PC)



Finishes - See our price list or website for finish availability.

DB4:030 © Frank Allart 2018